

PATHOLOGY WORKSTATION

DESCRIPTION

Pathological workstation is widely used in hospital pathology department, pathology laboratory, etc. Its ventilation system protects operator away from the harmful fumes produced by the formalin during sampling. The hot and cold-water system ensures it can adapt work in different climates. It is reliable quality, elegant appearance and fully functional, and equipped with high quality parts.

TECHNICAL PARAMETERS

MODEL	QCT-1500
Work Surface Height	900 mm
Exhaust Airflow Volume	500-600 m ³ /h
UV lamp	15 W, emission of 253.7 nm
LED lamp	9 W
Additional Illumination	5 W LED gooseneck spotlight
External Size	1500 x 750 x 1950 mm
Working Area Size	1395 x 430 x 900 mm
Gross Weight	300 kg
Material	Work Table: 304 stainless steel (S.S.) Main Body: 304 S.S.
Consumption	300 W
Power Supply	AC 110V±10%, 60Hz



Ecoshel reserves all the rights to changes in product design, if there are any design change, we will not inform in advance.



STANDARD ACCESSORIES

1. Adjustable spotlight
2. UV lamp
3. LED lamp
4. Waterproof sockets
5. S.S. water sink and tap
6. S.S. hangers
7. Active carbon filter
8. Pipe strap
9. Exhaust duct

KEY FEATURES

1. Suction inlet adopts louver-type. The upper mouth structure ensures above blower suction, avoiding air back-streaming.
2. Automatic flushing device, slightly right-side inclined worktable, easy to discharge of waste and cleaning.
3. Base cabinet is inward-concave type, convenient for sitting operation.
4. Exhaust air system, high-power suction device, low noise.
5. Optional pulverizer can completely smash the waste during test, to avoid blocking drainage pipes.

OPTIONAL ACCESSORIES

1. Pulverizer
2. Electrical water heater
3. Automatic induction hand dryer
4. Eye washer
5. Camera
6. Flex magnifier light
7. Laptop bracket

Ecoshel reserves all the rights to changes in product design, if there are any design change, we will not inform in advance.