

CIRCULATION BATH

DESCRIPTION

Water baths are an integral component of any general-use laboratory, needed in almost any experimental workflow; however, circulating water baths are ideal when temperature uniformity and control are particularly critical, such as when working with enzymes and in serological applications. Extensively used in petrochemical industry, metallurgy, chemical industry, physics, biology engineering, chemistry, pharmaceutical, life science, electronic instrument, plant laboratory, colleges, R&D institutes, etc.

TECHNICAL PARAMETERS

MODEL	SC-30B
Capacity	Approx. 21.2 L
Temperature range	RT+5°C to 90°C
Temperature stability	±0.5°C
Flow rate	6 L/min
Display	LCD display
Overall dimensions	Approx. Φ 305 x 595 mm
Inner tank size	Φ 305 x 300 mm
Opening dimension	Φ 150 mm
Gross weight	Approx. 17.7 kg
Power supply	AC 110V, 60Hz



Ecoshel reserves all the rights to changes in product design, if there are any design change, we will not inform in advance.



STANDARD ACCESSORIES

1. Plastic tubing
2. Drain valve
3. Lid of water bath

KEY FEATURES

1. External and internal circulation system.
2. Auditive alarm for overheating and when ending timer.
3. Soft keyboard and easy-to-use.
4. Compact and light design provide comfortable mobility.

Ecoshel reserves all the rights to changes in product design, if there are any design change, we will not inform in advance.