FUME CUPBOARD

DESCRIPTION

Fume Hood is used to protect operator from hazardous, corrosive, and toxic fumes which can be generated during chemical experiments. This cabinet protects operator from direct inhaling toxic vapors and dramatically reduces the risk of fire and explosion. By installing proper filter, it can also protect environment and prevent potentially dangerous substances from spreading into environment.

TECHNICAL PARAMETERS

MODEL

DFH15

Work Surface Height

Airflow Velocity

Front Window

Max Opening

Blower

Noise

UV Lamp

LED Lamp

External Size

Internal Size

Gross Weight

aross worgin

Material

Consumption

Power Supply

850 mm

0.3-0.8 m/s, air speed adjustable

Motorized

570 mm

Built-in centrifugal blower, speed adjustable

<60 dB

30 W. emission of 253.7 nm

16 W

1500 x 800 x 2345 mm

1320 x 670 x 750 mm

331 KQ

Front Window: 5 mm toughened glass

Work Table: Chemical resistant phenolic resin

Main Body and Base: Cold-rolled steel with anti-bacteria

powder coating

500 W

AC 110V±10%, 60Hz





Ecoshel reserves all the rights to changes in product design, if there are any design change, we will not inform in advance.

STANDARD ACCESSORIES

- Base cabinet
- 2. UV lamp
- 3. LED lamp
- 4. Water and gas taps
- 5. Water sink
- 6. Pipe strap
- 7. Exhaust duct

OPTIONAL ACCESSORY

1. Active carbon filter

KEY FEATURES

- 1. Easy-to-use soft keys of control panel.
- 2. Microprocessor control system, LED display.
- 3. Adjustable air speed: 9 levels.
- 4. Has two waterproof sockets.



Ecoshel reserves all the rights to changes in product design, if there are any design change, we will not inform in advance.

