

HORIZONTAL LAMINAR FLOW CABINET

DESCRIPTION

Laminar Flow Cabinet protects experimental material or samples, its main function is to make sure the accuracy of experiment at the operating area, but it could not protect the environment or operators. It creates a particle-free working environment by taking air through a filtration system and exhausting it across a work surface in a laminar or unidirectional air stream. This model is horizontal type Laminar Flow Cabinet.

TECHNICAL PARAMETERS

MODEL	ECO-H1500
Work Surface Height	750 mm
Airflow Velocity	0.3-0.45 m/s, air speed adjustable
HEPA Filter	99.999% efficiency at 0.3 μ m
Pre-Filter	Polyester fiber, washable
Noise	<65 dB
UV Lamp	30 W, emission of 253.7 nm
LED Lamp	16 W
External Size	1500 x 808 x 1690 mm
Internal Size	1400 x 500 x 600 mm
Gross Weight	185 kg
Material	Side Windows: 8 mm toughened glass Work Table: 304 stainless steel Main Body and Base: Cold-rolled steel with anti-bacteria powder coating
Consumption	300 W
Power Supply	AC 110V \pm 10%, 60Hz



Ecoshel reserves all the rights to changes in product design, if there are any design change, we will not inform in advance.



STANDARD ACCESSORIES

1. Waterproof sockets
2. Base stand
3. LED lamp
4. UV lamp
5. Hooks

KEY FEATURES

1. Universal caster with leveling feet.
2. Microprocessor control system, LCD Display.
3. Transparent side glass windows maximize light and visibility inside the cabinet, providing a bright and open working environment.

Ecoshel reserves all the rights to changes in product design, if there are any design change, we will not inform in advance.