DRYING OVEN/INCUBATOR

TECHNICAL PARAMETERS

MODEL

9065

Capacity

Temperature range

Temperature uniformity

Convection

Timei

Exterior size

Inner chamber size

Net weight

Consume power

Power supply

65 L

Incubator: RT+5°C to 80°C Drying oven: 80°C to 250°C

Incubator: ±0.5°C Drying oven: ±1.0°C

Forced and natural convection

0 - 9999 min

550 x 550 x 840 mm

400 x 360 x 450 mm

47 kn

Incubator: 400 W Drying oven: 1600 W

AC 110V, 60Hz

DESCRIPTION

This equipment has double function as drying oven and incubator. It has PID controller with over-temperature protection function, fan switch and LED digital display. It is widely used in labs of industrial enterprises, scientific research institutions, colleges and health and medicine units for drying, baking, melting, sterilizing, and curing, etc.





Ecoshel reserves all the rights to changes in product design, if there are any design change, we will not inform in advance.

STANDARD ACCESSORIES

1. Shelves

KEY FEATURES

- 1.
- 2.
- High efficiency and uniformity.
 PID controller, with over-temperature protection function.
 With oven/incubator change switch, forced convection switch and LED digital 3. display.
- 4.
- Auditive alarm for over-temperature and when ending timer. Function of drying and culturing can be switched freely for easy use. 5.



Ecoshel reserves all the rights to changes in product design, if there are any design change, we will not inform in advance.