

THERMOSTATIC WATER BATH

DESCRIPTION

Thermostatic water bath is applicable for distillation, concentration, drying and thermostatic heating of medical units, universities and colleges, scientific research units and laboratories of industrial and mining enterprises like chemical printing and dyeing enterprises and pharmaceutical enterprises.

TECHNICAL PARAMETERS

MODEL	DK-2000-III L
Volume	Approx. 14.6 L
Temperature range	RT+5°C to 100°C
Temperature motion	±0.5°C
Sensibility of temperature control	≤±1°C
Display error	≤±2.5°C
Timer	0 - 9999 min
Overall dimensions	Approx. 360 x 330 x 215 mm
Work bath dimensions	325 x 300 x 150 mm
Gross weight	Approx. 7.3 kg
Power	1000 W
Power supply	AC 110V, 60Hz



Ecoshel reserves all the rights to changes in product design, if there are any design change, we will not inform in advance.



STANDARD ACCESSORIES

1. Removable cover with four holes
2. Concentric ring covers
3. Drain valve

KEY FEATURES

1. A cover for the four holes water bath distributed in two rows, each with two holes.
2. Compact design for easy mobility.
3. Double LED display to display set time and bath temperature.
4. Soft keyboard and easy-to-use.

Ecoshel reserves all the rights to changes in product design, if there are any design change, we will not inform in advance.