

CIRCULATION BATH

TECHNICAL PARAMETERS

MODEL	SC-15
Capacity	15 L
Temperature range	RT +5°C to 100°C
Accuracy	±0.1°C
Display	LCD display
Overall dimensions	Approx. 320 x 370 x 510 mm
Bath size	240 x 300 x 200 mm
Bath open size	235 x 160 mm
Gross weight	Approx. 12.7 kg
Power	1000 W
Power supply	AC 110V, 60Hz

DESCRIPTION

Water baths are an integral component of any general-use laboratory, needed in almost any experimental workflow; however, circulating water baths are ideal when temperature uniformity and control are particularly critical, such as when working with enzymes and in serological applications. Extensively used in petrochemical industry, metallurgy, chemical industry, physics, biology engineering, chemistry, pharmaceutical, life science, electronic instrument, plant laboratory, colleges, R&D institutes, etc.



Ecoshel reserves all the rights to changes in product design, if there are any design change, we will not inform in advance.



STANDARD ACCESSORIES

1. Drain valve
2. Lid of water bath

KEY FEATURES

1. Overheating and overcurrent protections.
2. External and internal circulation system.
3. Control panel is touch-sensitive and easy-to-use.
4. Compact design and integrated handles on sides to mobility.

Ecoshel reserves all the rights to changes in product design, if there are any design change, we will not inform in advance.