

CIRCULATION BATH WITH COOLING SYSTEM

DESCRIPTION

Water baths are an integral component of any general-use laboratory, needed in almost any experimental workflow; however, circulating water baths are ideal when temperature uniformity and control are particularly critical, such as when working with enzymes and in serological applications. Extensively used in petrochemical industry, metallurgy, chemical industry, physics, biology engineering, chemistry, pharmaceutical, life science, electronic instrument, plant laboratory, colleges, R&D institutes, etc.

TECHNICAL PARAMETERS

MODEL	DC-2006
Capacity	6 L
Temperature range	-20°C to 100°C
Temperature stability	±0.1°C
Flow rate	0-15 L/min
Display	LCD touchscreen
Overall dimensions	340 x 390 x 660 mm
Work bath dimensions	200 x 260 x 140 mm
Open size	180 x 140 mm
Power	1450 W
Power supply	AC 110V, 60Hz



Ecoshel reserves all the rights to changes in product design, if there are any design change, we will not inform in advance.

STANDARD ACCESSORIES

1. Drain valve
2. Lid

KEY FEATURES

1. LCD touchscreen, intuitive control panel.
2. Audible alarm sounds when the timer ends.
3. Quick cooling with low noise.
4. Overheating and overcurrent protection.
5. Built-in handles on the sides allow for easy mobility.



Ecoshel reserves all the rights to changes in product design, if there are any design change, we will not inform in advance.