FORCED AIR DRYING OVEN

DESCRIPTION

LCD-65BE PLUS is widely used for drying, baking, melting, sterilizing, and curing in laboratories of industrial enterprises, scientific research institutions and universities. It has forced and natural convection for various applications.

TECHNICAL PARAMETERS

MODEL

LCD-65BE PLUS

Capacity	
Temperature range	
Temperature motion	
Convection	
Timer	
Exterior size	
Inner chamber size	
Net weight	
Power rating	
Power supply	

65 L
RT+10°C to 300°C
± 1°C
Forced and natural convection
0 - 9999 min
540 × 550 × 830 mm
400 × 360 × 450 mm
49 kg
1.6 kW
AC 110V, 60Hz





Ecoshel reserves all the rights to changes in product design, if there are any design change, we will not inform in advance.

STANDARD ACCESSORIES

1. Shelves

KEY FEATURES

- 1. Elegant design, made of mirror stainless steel.
- 2. LCD display, control panel is user-friendly.
- 3. Audible alarm for over-temperature and when time runs out.
- 4. Three speed fan control, adjustable for different requirements.
- 5. Accurate temperature control with PID digital temperature controller.
- 6. Test hole on the top for easy access to temperature probes.
- 7. Independent temperature limiter with temperature controller.





Ecoshel reserves all the rights to changes in product design, if there are any design change, we will not inform in advance.